



**NOTES:**

1. SEWER LATERAL SLOPES SHALL BE 1/4" PER FOOT MINIMUM.
2. INSTALL SEWER LATERAL AT RIGHT ANGLE TO PROPERTY LINE.
3. ALL TRENCHING WILL COMPLY WITH STATE OF CALIFORNIA DIVISION OF INDUSTRIAL SAFETY STANDARDS.
4. THE MAXIMUM LENGTH OF OPEN TRENCH SHALL BE 500 FT IN A EXISITNG STREET.
5. A CITY OF NEEDLES PERMIT WILL BE OBTAINED PRIOR TO ANY CONSTRUCTION WITHIN A CITY RIGHT-A-WAY.
6. ALL WORK WILL COMPLY WITH THE "STANDARD SPECIFICATION FOR PUBLIC WORKS CONSTRUCTION, SOUTHERN CALIFORNIA DISTRICT, SECTION 200".
7. TRAFFIC CONTROL DEVICES SHALL BE INSTALLED PER UNIFORM TRAFFIC CONTROL DEVICE MANUAL.

Detail No.

**ULD-2**



City of Needles  
**STANDARD DETAIL**

**UTILITY LOCATION  
STREET CROSS SECTION**

Revised

06/27/05

Detail No.

**ULD-2**